



Power of RFID

UHF RFID Serial Interface Reader/Writer ADB-522 (902-928 MHz)



ADB-522



Features

- Either Integral or 4 External Mono-static Antennas
- Serial Communications – RS232
- Frequencies cover all major markets
- 1W Output, 0-1W tuning at 1dB steps
- Multiple forward and reverse data link speeds
- Pre-scanned for Certification
- Dense Reader Mode
- Compact Credit Card Size
- Variable user memory access via API
- ≤ 10 ms Wake Up Time

Specifications

ADB-522	
Frequency	902.60~927.40 MHz, Frequency Hopping
RF Power	1 Watt Max (+30 dBm) w/ 20 dBi digital Control Range
Protocols	EPC C1G2, ISO 18000-6 B/C
Antenna Polarization	Linear Polarized
Antenna Gain & Impedance	12.4 dBi Typical and 50 Ohm
Antenna Configuration	Four MMCX (F) antenna connectors - Mono-static
Communications Interface	Serial - RS-232
Power Requirements	DC 13 V @ 2.0 A max
Operating Temperature	-30°C to +65°C (-22°F to +149°F)
Size	2.11"x4.25"x0.35"

Dimensions and Pin Diagram



* Note: Special license to operate this device may be required in certain countries. Adhere to local regulations where applicable.



18300 Sutter Blvd., Morgan Hill, CA 95037
 Tel: (408) 825-1100 Fax: (408) 782-7402
<http://www.awid.com>